

MFU-HW welding fume extractor with red arm

耳 Sectors Welding,

□ Applications: Mobile

↓ Issues Fumes

COD:

MFU21HWR0000000



 $Mobile\ extractors\ for\ welding\ fumes\ and\ micro-dust,\ high\ performance\ for\ professional\ use,\ with\ HEPA\ HI3\ 99.99\%\ absolute\ filtration$



Via Stroppiana, 15 - 10071 Borgaro torinese (Torino) Italy Tel. +39 011 4502031 – Fax +39 011 47 03 927 - info@secureair.it - www.secureair.it

Detailed description

Don't breathe in **fumes and micro-dusts released into the environment during welding!** Rely on HEPA H13 filtration to abate welding fumes and micro-dusts by using an **MFU welding fume extractor,** specifically designed to extract and filter fumes and micro-dusts generated by metal welding processes, filtering 99.99% of particles over 0.3µm. MFU series mobile extractors represent the ultimate in technology for the drastic reduction of risks derived from fumes and micro-dusts within professional work environments. The pollutants are quickly sucked in at the source thanks to the high-capacity hood and are then filtered 99.99% thanks to HEPA technology, a guarantee of micro-dust abatement from 0.3µm and up.

For this reason, the MFU welding fume extractor is certified W3 compliant for the filtration of carcinogens as per EN 15102.

Unique features of MFU

- Compact and maneuverable structure;
- Self-supporting suction arm with rigid pipes working length mt 2, 3 or 4;
- Room air recirculation with absolute H13 HEPA filtration 99.99%
- W3 certificate compliant for filtration of carcinogens;
- Electrical panel included on board as per EN 15102 standards;
- Indicator light for filter clogging warning;
- Hour meter for machine maintenance log keeping;
- Single-phase plug and cable with shuko socket requires no electrical installations, is ready to use;
- High-capacity suction hood with handle for easy positioning.

How it works

The welding fume extractor purifies the pollutants that pass through the system from the arm in the machine downward and are purified at 99.99% efficiency, the clean air is fed back into the room through grilles located at the bottom on the sides of the machine for maximum efficiency and energy saving.

Safety as per regulations

The clogging level of the filters is monitored by a control that alerts with a light signal when the filters need to be cleaned or replaced, so as to avoid continuing work without air filtration.

Construction

- Sturdy galvanized or painted steel support structure depending on the application, equipped with practical handles for handling;
- 4 pivoting wheels with brakes;
- Self-supporting suction arm of mt 2, 3 or 4 depending on the model;
- Electrical panel with ventilation on/off control, hour meter and filter clogging warning light;
- Single-suction centrifugal fan in version directly coupled to single-phase asynchronous motor.





ADVANTAGES

- Fast fume extraction close to the source due to high flow rate
- Mobile: allows a variety of welding spots to be reached
- Filtration with absolute filter eff. H13 ≥99.99% of particles over 0.3µm.
- 1500W single-phase power can be connected anywhere with a simple shuko socket



Advantages of buying with operational leasing in 12/24/36 or 48 convenient instalments

- No advance payments to be made, no pro-rata.
- First instalment on average at 30 days.
- Totally deducts rental fees for IRES purposes with no obligations arising from the minimum contract duration provided for by the T.U.
- Totally deducts royalties for IRAP purposes without distinction between capital and interest.
- Basel 2 advantage: thanks to the rental, the asset used is "off-asset" and therefore does not require corresponding assets.
- All-risk insurance included in the fees to cover possible claims.
- Fixed rate for the entire duration of the transaction.

Partner **BCC Lease**



Technical Data

Code	Power kW	Nominal flow rate m3 / h	Noise Db (A)	Weight kg	Arm length meters
MFU21HW2R000000	1,5	1500	73	102	2
MFU21HW3R000000	1,5	1500	73	102	3
MFU21HW4R000000	1,5	1500	73	102	4





Technical Data

Code	Power kW	Stage 1 filter	Stage 2 filter	Stage 3 filter
MFU21HWR0000000	1,5	metal anti-spark eff. G3	HEPA H13 ≥99,95% @ MPPS acc. to EN 1822:2009	10 kg activated carbon





Photogallery

















Accessories



Filtered air outlet connection MFU

KITSCARICESTMFU

Lateral connection diam. 200 mm for hose to discharge filtered air outside from MFU purifiers all.



10kg activated carbon filter kit for MFU and WFU

MFU18WECA100000

10kg (2x5kg) activated carbon filter kit for all WFUs and MFUs 16 -18 - HW



17kg activated carbon filter kit for MFU

MFU21WECA170001

Replacement filter kit for 17 kg activated carbon filter stage - for all MFU purifiers from 2021 onward. Refillable version.





Spare parts



Metal Filter Replacement - Stage 1 - MFU-HW

Metal Filter Replacement - Stage 1 - MFU-HW only



Replacement acrylic filter - Stage 2 - MFU-HW

Replacement acrylic filter - Stage 2 - MFU-HW only



Replacement filter H13 HEPA - Stage 3 - MFU-HW

Replacement H13 HEPA filter - Stage 3 - MFU-HW only



17kg activated carbon filter kit for MFU

Replacement filter kit for 17 kg activated carbon filter stage - for all MFU purifiers from 2021 onward. Refillable version.



10kg activated carbon filter kit for MFU and WFU

10kg (2x5kg) activated carbon filter kit for all WFUs and MFUs 16 -18 - HW





Via Stroppiana, 15 - 10071 Borgaro torinese (Torino) Italy
Tel. +39 011 4502031 – Fax +39 011 47 03 927 - info@secureair.it - www.secureair.it

Related products



MFU-HW welding fume extractor with superflex arm

MFU21HWXF000000

 $Mobile\ extractors\ for\ welding\ fumes\ and\ micro-dust, high\ performance\ for\ professional\ use, with\ HEPA\ H13\ 99.99\%\ absolute\ filtration$



MFU-HWF23 welding fume extractor double arm 3m

MFU21HW32F00000

Mobile welding fume extractor with superflex double arm, with filtration efficiency H13 99.99%.

