

# Table top welding fume extractor with AFT filter

📌 Sectors [Welding](#),

📌 Applications: [Fix](#)

📌 Issues [Fumes](#)



COD: AFT0000000000000

The **AFT tabletop fume extractor** captures fumes directly at the source through its special self-supporting flexible jointed hose before they can reach the operator's respiratory tract, as required by regulations.

The AFT system is the ideal solution for small welding operations.

## Detailed description

The AFT system is the ideal solution for small welding operations.

Pollutants are then filtered out by the BIA-class U.S.G.C.-certified polyester cartridge with 99% filtering efficiency and an activated carbon cartridge, both of which are integrated on the ejector port of the vacuum cleaner.

Its features result in:

- Space-saving
- Quiet
- Efficient
- Practical
- Can be oriented in all directions thanks to the rotating base
- Handy
- Extremely economical
- Lightweight

### Construction and technical data

- Stable swivel pedestal to rest on work surface
- High-efficiency centrifugal aspirator
- Special 100-diameter flexible hose on suction, self-supporting and extendable at will
- Polyester cartridge filter eff.99% on air expulsion
- On/off switch with single-phase 220V cable and plug
- Nominal flow rate 200 mc/h
- Noise level 50 dB(A) at 1.5 mt
- Power 75W
- Weight kg 7



## Technical Data

Code	Power kW	Nominal flow rate m <sup>3</sup> / h	Noise Db (A)	Weight kg	Flex tube	Cartridge type	Extractor
AFT000000000000	75	200	50	7	100 suction diameter, self-supporting and extendable at will	Polyester eff.99% on air expulsion	high efficiency centrifugal extractor



## Photogallery



## Spare parts



### Activated carbon replacement cartridge for AFT

Original replacement activated charcoal filter cartridge for AFT vacuum cleaner



### Polyester replacement cartridge for AFT

Original replacement polyester filter cartridge for AFT vacuum cleaner

