


Spacer for fixing SEQ fans on thin walls



↓ Applications: Fix

☐ Issues Odours

COD: DISSEQ000000000



Rectangular spacer for fixing on thin walls for SEQ model fans.


Detailed description

The spacer is 140mm thick for installation of the axial fan on very thin walls or panels (less than 200mm). This spacer flange is for being able to fix the fan when the wall or panel, on which they are to be mounted, is less than 200mm thick.



Via Stroppiana, 15 - 10071 Borgaro torinese (Torino) Italy Tel. +39 011 4502031 - Fax +39 011 47 03 927 - info@secureair.it - www.secureair.it

Accessories



Gravity damper for SE® axial fans

SERSEQ000000000

The SEQ axial fan gravity damper prevents heat loss when the fan is stopped, rain, wind and bird entry.



Via Stroppiana, 15 - 10071 Borgaro torinese (Torino) Italy
Tel. +39 011 4502031 – Fax +39 011 47 03 927 - info@secureair.it - www.secureair.it

Related products



SE@ axial panel fans

SEQ000000000000

Axial wall-mounted **fans** are ideal exhaust fans for applications where high air flow rates and installation with wall or panel mounting are needed. For example: ventilation of warehouses, gymnasiums, factories, parking lots, farms, cooling of electrical equipment, refrigeration equipment, etc.

