
IPE/HEA/HEB beam fastening kit

COD: KITIPEHEAHEB000

SECURE AIR®



Fastening kit for SMHS fans in HVLS version compatible with most popular IPE, HEA, HEB steel profiles.



Detailed description


Fastening kit for SMHS fans in HVLS version compatible with most popular IPE, HEA, HEB steel profiles. Supplied with fixing screws.





Photogallery

Modello	Gamma
IPE	da IPE180 a IPE600
HEA	da HEA100 a HEA400
HEB	da HEB100 a HEB300







Related products



HVLS APBG5 industrial 5-blade ceiling fan

SMHS00000000000

APBG5 5-Blade Industrial Ceiling Fan

- 5 Blades Extruded Aluminum Anodized Against Corrosion Constant Section
- Increased Air Distribution Cone
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters
- 3 Sizes with Diameters 3.6m / 5.4m / 7.3m
- Air Flow Rates up to 438,818 m3/h (AMCA230-99)
- 110 RPM Max
- Pot. Max Ass. 0.75 kW



HVLS APBG5S industrial 5-blade ceiling fan

SWHS00000000000

HVLS APBG5S industrial 5-Blade Ceiling Fan

- 5 Blades Extruded Aluminum Shaped Profile
- Narrow Cone Air Distribution
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters 3
- Sizes with Diameters 4m/5m/6m
- Air Flow Rates up to 529,464 m3/h (AMCA230-99)
- 120 RPM Max
- Pot. Max Ass. 1.4 kW
- Suitable for continuous duty S1



HVLS3 industrial 3-blade ceiling fan

SLHS00000000000

HVLS 3-Blade Industrial Ceiling Fans.

- 3 Blades Extruded in Anodized Aluminum against Corrosion with Constant **Cross Section**
- Precabled 3-phase Brushless EC motor equipped with Integrated Electronic System and EMC3 filters
- Sizes with Diameters 2.4m/3m/3.6m
- Air Flow Rates up to 134,271 m3/h (AMCA230-99)200
- Max RPM
- Pot. Max Ass. 0.7 kW
- Suitable for continuous duty S1.



