

# Control panel with anemometer and probe for temperature measurement

COD:

PNCANEMSND00000



Controller to control ventilation units according to the degree of temperature and wind speed.

## Detailed description

The control panel with anemometer and temperature measurement probe provides 3 modes of operation:

- **Mode A:** ventilation control according to wind speed by anemometer (accessory upon request) and fan lock according to temperature
- **Mode B:** ventilation control according to room temperature by temperature probe (supplied as standard) and fan lock according to wind speed
- **Mode C:** ventilation control according to room temperature via 2 temperature probes (additional probe on request) to manage winter destratification and summer comfort

The control controller includes:

- 1 temperature probe included
- On request: wind speed probe (anemometer)
- On request: additional temperature probe for operation mode C



## Dimensions

Code	Dimensions mm
PNCANEMSND00000	160x110x81

## Technical Data

Code	Power supply V	Power supply Hz
PNCANEMSND00000	0-10	50/60



## Related products



### SEQA1400 High Flow Axial Fan

SEQA140000000000

High-flow axial fans suitable for wall or overhead installation to create a uniform indoor climate and recirculate air in commercial and industrial buildings, farms, barns, and greenhouses.



### HVLS APBG5S industrial 5-blade ceiling fan

SWHS000000000000

HVLS APBG5S industrial 5-Blade Ceiling Fan

- 5 Blades Extruded Aluminum Shaped Profile
- Narrow Cone Air Distribution
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters 3
- Sizes with Diameters 4m / 5m / 6m
- Air Flow Rates up to 529,464 m<sup>3</sup>/h (AMCA230-99)
- 120 RPM Max
- Pot. Max Ass. 1.4 kW
- Suitable for continuous duty S1



### HVLS APBG5 industrial 5-blade ceiling fan

SMHS000000000000

APBG5 5-Blade Industrial Ceiling Fan

- 5 Blades Extruded Aluminum Anodized Against Corrosion Constant Section
- Increased Air Distribution Cone
- Three-phase Brushless EC motor equipped with Integrated Electronic System and EMC filters
- 3 Sizes with Diameters 3.6m / 5.4m / 7.3m
- Air Flow Rates up to 438,818 m<sup>3</sup>/h (AMCA230-99)
- 110 RPM Max
- Pot. Max Ass. 0.75 kW



### HVLS3 industrial 3-blade ceiling fan

SLHS000000000000

HVLS 3-Blade Industrial Ceiling Fans.

- 3 Blades Extruded in Anodized Aluminum against Corrosion with Constant Cross Section
- Precabled 3-phase Brushless EC motor equipped with Integrated Electronic System and EMC3 filters



- Sizes with Diameters 2.4m / 3m / 3.6m
- Air Flow Rates up to 134,271 m<sup>3</sup>/h (AMCA230-99)200
- Max RPM
- Pot. Max Ass. 0.7 kW
- Suitable for continuous duty S1.

